



INSTALLATION INSTRUCTIONS

Part Number YA-6504

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N Filtercharger® seals properly.

INSTALLATION

1. Unscrew the two screws and remove the intake inlet (2005-2006 models). (Fig. 1)
2. Remove the engine cover. (Fig. 2)
3. Remove the crankcase breather tube from the air box lid. (Fig. 3)
4. Unclip the air box lid retainer clips and remove the air box lid.
5. Remove the stock air filter.
6. Install the K&N Filtercharger® into the air box with the open end of the air filter pushed against the intake tube opening. (Fig. 4)
7. Carefully push down on the end of the K&N Filtercharger® until it snaps into the air filter locator tabs in the air box. (Fig. 5)

Note: In extremely dusty conditions apply K&N Sealing Grease or equivalent to the lip seal on the K&N Filtercharger®. (Fig. 6)

Available to purchase separately

Precharger Wrap; part number YA-6504PK

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6